

No Skidding®



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone (416) 667-1788 Fax (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571
We warehouse within the U.S. for our U.S. customers

NS75500 SERIES PHOTOLUMINESCENT TAPE GLOWS for 24+ HOURS HIGH TACK GRADE #75500

Description

Flexible laminated film coated with permanent acrylic pressure sensitive adhesive and backed with poly coated release liner. Safety grade photoluminescent material designed to glow 24+ hours. Product withstands UV-light and does not show significant degradation when used outdoors.



- A flexible laminated film that absorbs and stores energy from ambient light.
- In the event of a power failure or power outage this tape is immediately visible thereby providing people with a clearly illuminated evacuation route.
- Glows for 24 + hours and recharges within 15 minutes with normal lighting.
- Our photoluminescent tape is peel and stick and easily affixes to walls, columns, around door or window frames, handrails, along stairways and baseboards, it is ideal for your low-level emergency egress system.
- Is constructed from a flexible laminated film that is coated with permanent acrylic pressure sensitive adhesive and backed by poly-coated release liner.
- UV stable, and installation is a simple and position, peel of backing, and apply to dry, non oily surface.
- Available in 1"X30 ft, 2"X30 ft, 3"X30 ft and 6"X30 ft. In addition, 3" circles, 3" arrows and black, green, or red strips. Custom sizes & shapes are available upon request.

Limitations

The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Any liability we may have with respect to a product or its use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental and consequential damages.

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.

Product Data

Nominal Thickness: (Film/Adhesive)	.011" +/-10%
Release Liner:	.005"+/-10%

Adhesion Properties

PSTC-1 (modified) Peel Adhesion from Stainless Steel:	72-oz/24 hour dwell
PSTC-7 Shear Adhesion from Stainless Steel: (1/2" x 1/2", 500 grams)	>24 hours
Minimum Application Temperature:	50°F
Color:	White/Green
Emission Color:	Yellow/Green
Glow Properties:	24+ hours
DIN 67510 Xe Lamp 1000 Lx/5 min.	Time span necessary for afterglow brightness to diminish to 0.32 mcd/m ² (100 times the human eye perception limit)

All information and testing are based on our best experience and knowledge and does not constitute a warranty of products sold. All No Skidding materials are sold with the understanding that the users will independently determine suitability of the end use of our product. We recommend customers test bondability immediately upon lamination or after aging, either accelerated or after a period of time.

No Skidding®



www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571
We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&.O.E.